



## НАКРАЙНИК AGR С ВЪТРЕШЕН КОНУС 60°

КОД	DN	Inch	Резба	CH	A	L	PN /bar/
AGR 5 1/8"	5	3/16"	1/8"	14	20.5	45	415
AGR 5 1/4"	5	3/16"	1/4"	19	26	51	415
AGR 6 1/8"	6	1/4"	1/8"	14	20.5	49	415
AGR 6 1/4"	6	1/4"	1/4"	19	27	55	450
AGR 6 3/8"	6	1/4"	3/8"	22	29	57	450
AGR 6 1/2"	6	1/4"	1/2"	27	32	60	450
AGR 8 1/4"	8	5/16"	1/4"	19	27	55	350
AGR 8 3/8"	8	5/16"	3/8"	22	29	57	350
AGR 8 1/2"	8	5/16"	1/2"	27	32	60	350
AGR 10 1/4"	10	3/8"	1/4"	19	27	57	450
AGR 10 3/8"	10	3/8"	3/8"	22	29	59	450
AGR 10 1/2"	10	3/8"	1/2"	27	32	62	450
AGR 12 3/8"	12	1/2"	3/8"	19	29	62	415
AGR 12 1/2"	12	1/2"	1/2"	27	33	66	415
AGR 12 5/8"	12	1/2"	5/8"	30	34.5	67.5	415
AGR 12 3/4"	12	1/2"	3/4"	32	36	69	415
AGR 16 1/2"	16	5/8"	1/2"	27	33	69	350
AGR 16 5/8"	16	5/8"	5/8"	30	34.5	70.5	350
AGR 16 3/4"	16	5/8"	3/4"	32	36	72	350
AGR 20 1/2"	20	3/4"	1/2"	27	34	75	350
AGR 20 5/8"	20	3/4"	5/8"	30	36	77	350
AGR 20 3/4"	20	3/4"	3/4"	32	37	78	350
AGR 20 1"	20	3/4"	1"	38	40	80	350
AGR 25 3/4"	25	1"	3/4"	32	38	93	280
AGR 25 1"	25	1"	1"	38	40	95	280
AGR 25 1.1/4"	25	1"	1.1/4"	50	45	100	280
AGR 32 1.1/4"	32	1.1/4"	1.1/4"	50	46	106	210
AGR 32 1.1/2"	32	1.1/4"	1.1/2"	55	46	107	210
AGR 40 1.1/2"	40	1.1/2"	1.1/2"	55	46	117	185
AGR 40 2"	40	1.1/2"	2"	70	53	124	185
AGR 50 2"	50	2"	2"	70	54	134	165