



Накрайник DKR-F BSP уплътнение на челна повърхност

КОД	DN	Inch	Резба	CH	A	L	PN /bar/
DKR-F 6 1/4"	6	1/4"	1/4"	19	14	42	450
DKR-F 6 3/8"	6	1/4"	3/8"	22	15	43	450
DKR-F 8 3/8"	8	5/16"	3/8"	22	15	43	350
DKR-F 10 3/8"	10	3/8"	3/8"	22	16	46	450
DKR-F 10 1/2"	10	3/8"	1/2"	27	17	47	450
DKR-F 12 1/2"	12	1/2"	1/2"	27	17	50	415
DKR-F 12 5/8"	12	1/2"	5/8"	28	17	50	415
DKR-F 12 3/4"	12	1/2"	3/4"	32	19	52	415
DKR-F 16 5/8"	16	5/8"	5/8"	28	17	53	350
DKR-F 16 3/4"	16	5/8"	3/4"	32	20	56	350
DKR-F 20 3/4"	20	3/4"	3/4"	32	21	62	350
DKR-F 20 1"	20	3/4"	1"	38	22	63	350
DKR-F 25 1"	25	1"	1"	38	23	78	280
DKR-F 32 1.1/4"	32	1.1/4"	1.1/4"	50	26	87	210