



Накрайник ORFS – АК

с гумено челно уплътнение

КОД	DN	Inch	Резба	CH	A	L	PN /bar/
AK 6 9/16"	6	1/4"	9/16"	17	24	52	450
AK 6 11/16"	6	1/4"	11/16"	19	27.5	55.5	450
AK 8 11/16"	8	5/16"	11/16"	19	27.5	55.5	350
AK 10 11/16"	10	3/8"	11/16"	19	27.5	57.5	445
AK 10 13/16"	10	3/8"	13/16"	22	30.5	60.5	445
AK 10 1"	10	3/8"	1"	27	33.5	63.5	445
AK 12 13/16"	12	1/2"	13/16"	27	34	67	415
AK 12 1"	12	1/2"	1"	27	31.5	67	415
AK 12 1.3/16"	12	1/2"	1.3/16"	32	36	68.5	415
AK 16 1"	16	5/8"	1"	27	34	70	350
AK 16 1.3/16"	16	5/8"	1.3/16"	32	37	73	350
AK 20 1.3/16"	20	3/4"	1.3/16"	32	38	79	350
AK 20 1.7/16"	20	3/4"	1.7/16"	41	38.5	79.5	350
AK 25 1.7/16"	25	1"	1.7/16"	41	39.5	94	280
AK 32 1.11/16"	32	1.1/4"	1.11/16"	46	40	101	210
AK 40 2"	40	1.1/2"	2"	55	43	114	185